

BARRAS REDONDA DE LATON		
ALEACION: C-360 NORMA: A.S.T.M B-16		
LARGO DE 3.66 MTS		
DIAMETRO	MILIMETROS	PESO X PZA
1/8	3.2	0.2452
5/32	4.0	0.3843
3/16	4.8	0.5527
7/32	5.5	0.7540
1/4	6.4	0.9845
5/16	7.9	1.5372
3/8	9.5	2.2143
7/16	11.1	3.0158
1/2	12.7	3.9382
9/16	14.3	4.9849
5/8	15.8	6.1525
11/16	17.5	7.4481
3/4	19.0	8.8645
13/16	20.6	10.4017
7/8	22.2	12.0634
15/16	23.8	13.8494
1	25.4	15.7563
1 1/16	27.0	17.7876
1 1/8	28.6	19.9433
1 3/16	30.2	22.2199
1 1/4	31.7	24.6208
1 3/8	34.9	29.7887
1 1/2	38.1	35.4544
1 3/4	44.4	48.2571
2	50.8	63.0106
2 1/4	57.1	79.7917
2 1/2	63.5	98.4650
2 3/4	69.8	119.1696
3	76.2	141.825
3 1/4	82.6	166.4568
3 1/2	88.9	193.0504
4	101.6	252.1483

BARRAS CUADRADA DE LATON		
ALEACION: C-360 NORMA: A.S.T.M B-16		
LARGO DE 3.66 MTS		
DIAMETRO	MILIMETROS	PESO X PZA
1/8	3.2	0.3147
5/32	4.0	0.4904
3/16	4.8	0.7063
1/4	6.4	1.2553
5/16	7.9	1.9581
3/8	9.5	2.8218
7/16	11.1	3.8393
1/2	12.7	5.0178
9/16	14.3	6.3501
5/8	15.8	7.8360
11/16	17.5	9.4794
3/4	19.0	11.2837
13/16	20.6	13.2455
7/8	22.2	15.3610
15/16	23.8	17.6338
1	25.4	20.0604
1 1/16	27.0	22.6480
1 1/8	28.6	25.3930
1 3/16	30.2	28.2918
1 1/4	31.7	31.3442
1 3/8	34.9	37.9285
1 1/2	38.1	45.1424
1 3/4	44.4	61.4367
2	50.8	80.2821

BARRAS HEXAGONAL DE LATON		
ALEACION: C-360 NORMA: A.S.T.M B-16		
LARGO DE 3.66 MTS		
DIAMETRO	MILIMETROS	PESO X PZA
1/8	3.2	0.2708
5/32	4.0	0.4246
3/16	4.8	0.6112
1/4	6.4	1.0870
5/16	7.9	1.6982
3/8	9.5	2.4449
7/16	11.1	3.3269
1/2	12.7	4.3444
9/16	14.3	5.4937
5/8	15.8	6.7856
11/16	17.5	8.2130
3/4	19.0	9.7759
13/16	20.6	11.4704
7/8	22.2	13.3041
15/16	23.8	15.2695
1	25.4	17.3740
1 1/16	27.0	19.6176
1 1/8	28.6	21.9893
1 3/16	30.2	24.5000
1 1/4	31.7	27.1462
1 3/8	34.9	32.8485
1 1/2	38.1	39.0925
1 3/4	44.4	53.2127
2	50.8	69.4924