

LAMINAS DE COBRE ELECTROLITICO						
ALEACION: C- 11000 SUAVE, SEMIDURO Y DURO			NORMA: A.S.T.M B-152			
ESPESOR	PULGADAS	MILIMETROS	PIES	METROS	PESO X M2	PESO X PZA
1/4	0.250	6.3500	3 X 10	.91 X 3.05	56.596	157.738
			3 X 8	.91 X 2.44		126.191
3/16	0.188	4.7625	3 X 10	.91 X 3.05	42.56	118.619
			3 X 8	.91 X 2.44		94.895
5/32	0.156	3.9700	3 X 10	.91 X 3.05	35.316	98.429
			3 X 8	.91 X 2.44		78.743
1/8	0.125	3.1750	3 X 10	.91 X 3.05	28.298	78.869
			3 X 8	.91 X 2.44		63.095
3/32	0.094	2.3825	3 X 10	.91 X 3.05	21.28	59.309
			3 X 8	.91 X 2.44		47.447
14	0.083	2.1082	3 X 10	.91 X 3.05	18.79	52.369
			3 X 8	.91 X 2.44		41.896
16	0.065	1.6510	3 X 10	.91 X 3.05	14.71	41.012
			3 X 8	.91 X 2.44		32.81
18	0.049	1.2446	3 X 10	.91 X 3.05	11.093	30.917
			3 X 8	.91 X 2.44		24.734
20	0.035	0.8890	3 X 10	.91 X 3.05	7.923	22.082
			3 X 8	.91 X 2.44		17.666
22	0.028	0.7112	3 X 10	.91 X 3.05	6.339	17.59
			3 X 8	.91 X 2.44		14.134
24	0.022	0.5588	3 X 10	.91 X 3.05	4.98	14.200
			3 X 8	.91 X 2.44		11.104
26	0.018	0.4572	3 X 10	.91 X 3.05	4.075	11.31
			3 X 8	.91 X 2.44		9.086
			2 X 8	.61 X 2.44		6.15

LAMINA EN ROLLO DE COBRE ELECTROLITICO				
ESPESOR	PULGADAS	MILIMETROS	ANCHO	PESO X M2
26	0.018	0.4572	61	4.075
28	0.014	0.3556	61	3.173
30	0.012	0.3048	61	2.718
32	0.009	0.2286	20	2.041
34	0.007	0.1778	20	1.587
36	0.004	0.1016	15	0.9