

<b>LAMINAS DE LATON</b>						
<b>ALEACION: C-2600 / C-22 (NORMA: A.S.T.M B-36)</b>				<b>TEMPLE: SUAVE SEMIDURO Y DURO</b>		
<b>ESPESOR</b>	<b>PULGADAS</b>	<b>MILIMETROS</b>	<b>PIES</b>	<b>METROS</b>	<b>PESO X M2</b>	<b>PESO X PZA</b>
4	0.238	6.0452	2 X 4	.61 X 1.22	51.194	38.099
6	0.203	5.1562	2 X 4	.61 X 1.22	43.665	32.495
8	0.165	4.1910	2 X 4	.61 X 1.22	35.492	26.413
10	0.134	3.4036	2 X 4	.61 X 1.22	28.823	21.45
12	0.109	2.7686	2 X 4	.61 X 1.22	23.446	17.449
14	0.083	2.1082	2 X 4	.61 X 1.22	17.853	13.286
16	0.065	1.6510	2 X 8	.61 X 2.44	13.982	21.323
18	0.049	1.2446	2 X 8	.61 X 2.44	10.540	16.074
20	0.035	0.8890	2 X 8	.61 X 2.44	7.529	11.482
22	0.028	0.7120	2 X 8	.61 X 2.44	6.023	9.185
24	0.022	0.5588	2 X 8	.61 X 2.44	4.732	7.216
26	0.018	0.4572	2 X 8	.61 X 2.44	3.872	5.905
28	0.014	0.3556	2 X 4	.61 X 1.22	3.011	2.241
30	0.012	0.3048	2 X 4	.61 X 1.22	2.581	1.921

<b>LAMINA EN ROLLO LATON</b>					
<b>ESPESOR</b>	<b>PULGADAS</b>	<b>MILIMETROS</b>	<b>ANCHO</b>	<b>PESO X M2</b>	<b>TEMPLE</b>
18	0.049	1.2446	61	10.54	RECOCIDO
20	0.035	0.8890	61	7.529	RECOCIDO
22	0.028	0.7112	61	6.023	RECOCIDO
24	0.022	0.5588	61	4.732	RECOCIDO
26	0.018	0.4572	61	3.872	RECOCIDO
28	0.014	0.3556	61	3.011	RECOCIDO
30	0.012	0.3048	61	2.581	RECOCIDO
32	0.009	0.2286	20	1.936	RECOCIDO
34	0.007	0.1778	20	1.506	SEMIDURO
36	0.004	0.1016	20	0.860	SEMIDURO