

SOLERAS DE LATON				
ALEACION: C-11000 NORMA: A.S.T.M B-187				
LARGO DE 3.66 MTS		TEMPLE: SUAVE, SEMIDURO, DURO		
PULGADAS		MILIMETROS		PESO X PIEZA
ESPEJOR	ANCHO	ESPEJOR	ANCHO	
1/16	1/4	1.6	6.4	0.315
	3/8		9.5	0.472
	1/2		12.7	0.626
	5/8		15.8	0.783
	3/4		19.0	0.941
	1		25.4	1.252
1/8	1/4	3.2	6.4	0.656
	3/8		9.5	0.994
	1/2		12.7	1.255
	5/8		15.8	1.566
	3/4		19.0	1.881
	1		25.4	2.507
	1 1/4		31.7	3.137
	1 1/2		38.1	3.762
	1 3/4		44.4	4.388
	2		50.8	5.018
	4		101.6	10.032
3/16	1/4	4.8	6.4	0.941
	3/8		9.5	1.1413
	1/2		12.7	1.881
	5/8		15.8	2.353
	3/4		19.0	2.822
	1		25.4	3.762
	1 1/4		31.7	4.703
	1 1/2		38.1	5.644
	1 3/4		44.4	6.584
	2		50.8	7.525
	2 1/2		63.5	9.406
	3		76.2	11.287
	4		101.6	15.05

SOLERAS DE LATON				
ALEACION: C-11000 NORMA: A.S.T.M B-187				
LARGO DE 3.66 MTS		TEMPLE: SUAVE, SEMIDURO, DURO		
PULGADAS		MILIMETROS		PESO X PIEZA
ESPELOR	ANCHO	ESPELOR	ANCHO	
1/4	3/8	6.4	9.5	1.881
	1/2		12.7	2.507
	5/8		15.8	3.137
	3/4		19.0	3.762
	1		25.4	5.018
	1 1/4		31.7	6.27
	1 1/2		38.1	7.525
	1 3/4		44.4	8.78
	2		50.8	10.032
	2 1/2		63.5	12.539
	3		76.2	15.05
4	101.6	20.064		
3/8	1/2	9.5	12.7	3.762
	5/8		15.8	4.703
	3/4		19.0	5.644
	1		25.4	7.525
	1 1/4		31.7	9.406
	1 1/2		38.1	11.287
	1 3/4		44.4	13.169
	2		50.8	15.05
	2 1/2		63.5	18.812
	3		76.2	22.575
4	101.6	30.1		
1/2	1	12.7	25.4	10.032
	1 1/2		38.1	15.05
	2		50.8	20.064
	2 1/2		63.5	25.082
	3		76.2	30.1
	4		101.6	40.132
1	2	25.4	50.8	40.55
	3		76.2	60.35
	4		101.6	80.85